

ROLLING BEARING

Publication number: JP7027139

Publication date: 1995-01-27

Inventor: MURAKAMI YASUO; SEKINO KAZUO; MITAMURA NOBUAKI

Applicant: NIPPON SEIKO KK

Classification:

- International: C21D9/40; C22C38/00; C22C38/18; C23C8/32; F16C33/32; F16C33/62; C21D9/40; C22C38/00; C22C38/18; C23C8/06; F16C33/30; F16C33/62; (IPC1-7): F16C33/62; C21D9/40; C22C38/00; C22C38/18; C23C8/32; F16C33/32

- European:


Application number: JP19940098926 19940512

Priority number(s): JP19940098926 19940512; JP19930111950 19930513

Report a data error here

Abstract of JP7027139

PURPOSE: To provide a rolling bearing by which both excellent dimensional stability and the long rolling service life can be held under conditions where a temperature is high and a foreign matter is mixed in lubricant in the bearing. **CONSTITUTION:** When prescribed heat treatment is applied to an inner ring, an outer ring and a rolling body composed of alloy steel containing C by 0.10 to 1.00 weight %, Cr by 0.50 to 3.00 weight %, Si by 0.15 to 1.00 weight % and Mn by 0.20 to 1.50 weight % at respective ratios, an average residual austenite quantity of the inner ring among the inner ring and the outer ring can be set not more than 4 volume %, and an average residual austenite quantity of the rolling body can be set in 20 to 30 volume %.



Data supplied from the esp@cenet database - Worldwide